

Accessories



LF/B6 MANUAL CALL POINT

Supply voltage : 24 V DC
 Electrical monitoring : 470R series resistor
 Colour : Red
 Operating temperature : -20° C to + 80° C



LF/B10 MANUAL CALL POINT (With Cover)

Supply voltage : 24 V DC
 Electrical monitoring: 470R Series resistor
 Colour : Red
 With transparent cover



LF/RI REMOTE INDICATOR

Nominal voltage : 24 V DC
 Alarm indicator : 2x8mm red LED
 Colour : White
 Weight : 100 grams



LF/SN SOUNDER

Nominal voltage : 24 V DC
 Current : 16 mA
 Colour : Red
 Sound output : 100dBA @ 1 mtr.
 Weight : 300 grams



LF/SI SIREN

Nominal voltage : 24 V DC
 Current : 28 mA
 Colour : White
 Sound output : 105dBA @ 1 mtr.



LF/SS SIREN WITH STROBE

Nominal voltage : 24 V DC
 Current : 28 mA
 Colour : Red
 Sound output : 105dBA @ 1 mtr.



LF/XB XENON BEACON

Nominal voltage : 24 V DC
 Current : 40 mA
 Colour : Red
 Flash frequency : 1Hz
 Flash energy : 0.7j
 Weight : 300 grams



LF/AS ABORT SWITCH

Supply Voltage : 24 V DC
 Contacts : NO, NC
 Colour : Available in different colours
 Operating Temperature: -20°C to +80°C



LF/EL EMERGENCY LIGHT

Supply voltage : 110 or 220V AC, 50/60Hz
 Battery : 6V, 4Ah sealed
 Rechargeable
 Lamp : 6V, 3W x 2
 Colour : White



LF/RS MANUAL RELEASE STATION

Supply Voltage : 24 V DC
 Electrical Monitoring : 470R series resistor
 Operating Temperature : -20°C to +80°C
 Colour : Yellow
 with transparent cover (optional)



LFB6 / LFB8

Alarm Bell 6" & 8"
 Normal Voltage 24 V DC
 Current: 60mA
 Colour: Red

Model	Size	Sound Output
LFB6	6"	85 dBA @ 1 mtr.
LFB8	8"	87 dBA @ 1 mtr.
LFB6W	6"	87 dBA @ 1 mtr.
LFB8W	8"	87 dBA @ 1 mtr.

Weatherproof back box available on request



Lichfield Fire & Safety Equipment Co. Ltd

2nd Floor, Suite 4, Saturn Centre, Spring Road, Ettingshall, Wolverhampton, WV4 6JX, United Kingdom.
 Tel: +44 (0) 8700664401 Fax: +44 (0) 8700664402
 E-mail: info@lifeco-uk.com www.lifeco-uk.com
 Registration No. 3718799 VAT No. 770056835

