UL Product **iQ**™



HMRZ.EX6197 - Gate Valves

Gate Valves

See General Information for Gate Valves

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

EX6197

UNIT 8, CALIBRE INDUSTRIAL PARK LACHES CLOSE FOUR ASHES WOLVERHAMPTON, WV10 7DZ UNITED KINGDOM

Pattern	Model	Size, in.	End Configuration	Rated Pressure, psig
NRS	3288-300-FLF, 3288-300-GLF, 3288- 300-FxGLF	2.5	Flanged, Grooved, Flanged by Grooved	300
NRS	3288-300-FLF, 3288-300-GLF, 3288- 300-MJLF, 3288-300-FxGLF, 3288-300- FxMJLF	3	Flanged, Grooved, Flanged by Grooved, Mechanical Joint, Flanged by Mechanical Joint	300
NRS	3288-300-FLF, 3288-300-GLF, 3288- 300-MJLF, 3288-300-FxMJLF	4, 6, 8, 10, 12	Flanged, Grooved, Mechanical Joint, Flange/Mechanical Joint	300
NRS	3288-300-FLF	5	Flanged	300
NRS	3288-300-GLF	4, 5, 6, 8, 10, 12	Grooved by Grooved	300
NRS	3188-250-FLF, 3188-250-MJLF, 3188-250-FxMJF	14, 16, 18	Flanged, Mechanical, Flanged by Mechanical	250
NRS	3188-200-FLF, 3188-200-MJLF, 3188-200-FxMJF	20, 24	Flanged, Mechanical, Flanged by Mechanical	200
NRS	3288-200-FLF	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	200
NRS	3288-250-FLF	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	250
OS&Y	3299-300-FLF, 3299-300-FxGLF, 3299-300-GLF	2-1/2, 3, 4, 5, 6, 8, 10, 12	Flanged, Grooved, Flanged by Grooved	300
OS&Y	3199-250-FLF, 3199-250-MJLF, 3199-250-FxMJF	14, 16, 18	Flanged, Mechanical, Flanged by Mechanical	250

OS&Y	3199-200-FLF, 3199-200-MJLF, 3199-200-FxMJF	20, 24	Flanged, Mechanical, Flanged by Mechanical	200
OS&Y	3299-200-FLF	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	200
OS&Y	3299-250-FLF	2-1/2, 3, 4, 6, 8, 10, 12	Flanged	250

Last Updated on 2015-02-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"