



HBOR.EX26732 - Hydrants

Hydrants

See General Information for Hydrants

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

EX26732

UNIT 8, CALIBRE INDUSTRIAL PARK
LACHES CLOSE FOUR ASHES
WOLVERHAMPTON, WV10 7DZ UNITED KINGDOM

Base-valve design:

Model	Base-valve Size, in.	Hose Outlet (No. of Outlets), in.	Pumper Outlet (No. of Outlets), in.	Rated Pressure, psig
LF-FM1510	5-1/4	(2) 2-1/2	(1) 4-1/2	250

Model LF-FM1510 hydrant may be supplied with a 2-1/2 in. flanged monitor elbow.

Model LF-FM1510 is a "traffic type" when equipped with a breakaway traffic flange.

Wet-barrel design:

Model	Hose Outlet (No. of Outlets), in.	Pumper Outlet (No. of Outlets), in.	Rated Pressure, psig
LF-WBH	(2) 2-1/2	(1)4 or 4-1/2 in threaded connection or 5 in. nonthreaded	250

Trademark and/or Tradename:



Last Updated on 2019-10-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"