

Hose Valves

Hose valves of 1 1/2 in. (38 mm) may be used on connections from sprinkler systems; 2 1/2 in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle

Model AH15, AH20, AH25, AH30, RV-AH20, RV-AH30, RV-AH15, RV-AH25

Model A angle hose valves, standard and pressure restricting types, in sizes 1-1/2 (38 mm) and 2-1/2 (64 mm) inch NPS.

<i>Model</i>	<i>Component Description</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>Nominal Size, in. (mm)</i>
AH15	Standard Angle Valve with double female connection	300 (2070)	1-1/2 (38)
AH20	Standard Angle Valve with female to male connection	300 (2070)	1-1/2 (38)
AH25	Standard Angle Valve with double female connection	300 (2070)	2-1/2 (64)
AH30	Standard Angle Valve with female to male connection	300 (2070)	2-1/2 (64)
RV-AH20	Pressure Restricting Angle Valve with female to male connection	175 (1205)	1-1/2 (38)
RV-AH30	Pressure Restricting Angle Valve with female to male connection	175 (1205)	2-1/2 (64)
RV-AH15	Pressure Restricting Angle Valve with female to female connection	175 (1205)	1-1/2 (38)
RV-AH25	Pressure Restricting Angle Valve with female to female connection	175 (1205)	2-1/2 (64)

Company Name:	Lichfield Fire & Safety Equipment Co Ltd
Company Address:	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
Company Website:	http://www.lifeco-uk.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved