

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Fig. 3288-200-FLF, Fig. 3288-200-GLF, Fig. 3288-200-FxMJLF, Fig. 3288-200-MJLF, Fig. 3288-200-FxGLF

Fig. 3288 Resilient Seated Gate Valve. Available with an indicator post flange. Rated Working Pressure 200 psi (1380 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3288-200-FLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3288-200-GLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove × Groove (ANSI, ISO, JIS)
Fig. 3288-200-FxMJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Mechanical Joint

Fig. 3288-200-MJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Mechanical Joint
Fig. 3288-200-FxGLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove

<b>Company Name:</b>	Lichfield Fire & Safety Equipment Co Ltd
<b>Company Address:</b>	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
<b>Company Website:</b>	<a href="http://www.lifeco-uk.com">http://www.lifeco-uk.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Fig. 3288-250-FLF, Fig. 3288-250-GLF, Fig. 3288-250-FxMJLF, Fig. 3288-250-MJLF, Fig. 3288-250-FxGLF

Fig. 3288 Resilient Seated Gate Valve. Available with an indicator post flange. Rated Working Pressure 250 psi (1725 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3288-250-FLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3288-250-GLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove × Groove (ANSI, ISO, JIS)
Fig. 3288-250-FxMJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Mechanical Joint

Fig. 3288-250-MJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Mechanical Joint
Fig. 3288-250-FxGLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove

<b>Company Name:</b>	Lichfield Fire & Safety Equipment Co Ltd
<b>Company Address:</b>	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
<b>Company Website:</b>	<a href="http://www.lifeco-uk.com">http://www.lifeco-uk.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Fig. 3288-300-FLF, Fig. 3288-300-GLF, Fig. 3288-300-FxMJLF, Fig. 3288-300-MJLF, Fig. 3288-300-FxGLF

Fig. 3288 Resilient Seated Gate Valve. Available with an indicator post flange. Rated Working Pressure 300 psi (2070 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3288-300-FLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3288-300-GLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Groove × Groove (ANSI, ISO, JIS)
Fig. 3288-300-FxMJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Mechanical Joint

Fig. 3288-300-MJLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Mechanical Joint
Fig. 3288-300-FxGLF	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

<b>Company Name:</b>	Lichfield Fire & Safety Equipment Co Ltd
<b>Company Address:</b>	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
<b>Company Website:</b>	<a href="http://www.lifeco-uk.com">http://www.lifeco-uk.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved