

TECHNICAL DATA SHEET

for use by Architects & Engineers

Fire Blanket

Model No: LF-FB/1.0x1.0, LF-FB/1.2x1.0, LF-FB/1.2x1.2, LF-FB/1.2x1.8, LF-FB/1.8x1.8



Features

- Pack fits snugly to wall
- Simple to use
- Absolutely reliable
- Maintenance free
- Choice of container colour
- Clear pictorial instructions
- 12 month guarantee
- Choice of sizes
- Easy storage and packing

Description

Different sizes and colours are available to suit domestic or industrial use. When removed from the container the blanket is held in the shield position, protecting the user from the fire. When draped over a fire the blanket starves the fire of oxygen, leading to rapid extinction. Topspec Fire Blankets can be used to wrap around a person whose clothes are on fire and can also be used to wrap around a hot or burning object for removal to a safe place.

TOPSPEC EURO is a Fire Blanket specifically designed and manufactured to the new European Standard for Fire Blankets. Topspec Euro has better drapability than ever before whilst the efficient and durable Fire Blanket gives outstanding extinguishing power. Topspec Euro is fitted with flame proof handles and uses Kevlar thread to ensure the blanket retains its integrity, giving the user confidence in the fiercest of fires. Topspec Euro is fully approved and BSI Kitemarked.

TOPSPEC STERLING is manufactured from a heavier weight cloth than Topspec Euro. It is fully approved and independently tested by BSI Kitemarked. It utilises a full weight cloth which gives the user confidence in the fiercest of fires combined with outstanding extinguishing power. Topspec Sterling is fitted with flame proof handles and uses Kevlar thread to ensure the blanket retains its integrity.

The Topspec Euro, Topspec Sterling and Budget range of fire blankets are completely asbestos free and are non-respirable and non-irritant. They are extremely resistant to tearing and drape easily. They are substantially more robust than other materials such as non-woven or un-coated fabrics which degrade rapidly or even burn.

The Topspec range of Fire Blankets are available in a one piece IM pack (as shown overleaf) or Super Slim.

Packing Specification

TOPSPEC EURO			Cartons of 20
Size (m)	Gross kg	Net kg	Measurements
1.0 x 1.0	12	11	34 x 42 x 30 cm
1.2 x 1.0	13	12	34 x 42 x 30 cm
1.2 x 1.2	16	15	34 x 42 x 30 cm
1.8 x 1.2	21	20	39 x 30 x 38 cm
1.8 x 1.8*	16	15	48 x 20 x 32 cm

1.8 x 1.8* packed in cartons of 10

TOPSPEC STERLING			Cartons of 20
Size (m)	Gross kg	Net kg	Measurements
1.0 x 1.0	18	17	34 x 42 x 30 cm
1.2 x 1.0	20	19	34 x 42 x 30 cm
1.2 x 1.2	22	21	34 x 42 x 30 cm
1.8 x 1.2	31	30	39 x 30 x 38 cm
1.8 x 1.8*	25	24	55 x 20 x 32 cm

1.8 x 1.8* packed in cartons of 10

Sizes Available

Topspec	Budget
1.0 m x 1.0 m	0.9 m x 0.9 m
1.2 m x 1.0 m	0.9 m x 1.2 m
1.2 m x 1.2 m	1.2 m x 1.2 m
1.8 m x 1.2 m	1.8 m x 1.2 m
1.8 m x 1.8 m	1.8 m x 1.8 m

TECHNICAL DATA SHEET

for use by Architects & Engineers



Fire Blanket

Model No: LF-FB/1.0x1.0, LF-FB/1.2x1.0, LF-FB/1.2x1.2, LF-FB/1.2x1.8, LF-FB/1.8x1.8

Features

Model	Base Fabric	Fabric Weight (gm/m ²)	Coating Type	Coating Weight (gm/m ²)	Blanket Weight (gm/m ²)	BS EN Approved	BS Kitemarked	BAFE Approved
Topspec Euro	Glass Fibre	200	Silicon Rubber	35 x 2	270	Yes	Yes	Yes
Topspec Sterling	Glass Fibre	430	Silicon Rubber	35 x 2	500	Yes	Yes	Yes
Budget	Glass Fibre	430	None	N/A	430	No	No	No