

Optional Accessories



Wall Plates

The wall plates are constructed of corrosion resistant brass with marking "AUTO SPKR" and "FIRE DEPT CONNECTION"

Features

- The brass seat is integrated with brass body
- 2.5" swivels are pin lug design for easy operation
- Compatible with local fire service requirements

Description

LIFECO FM Approved and UL listed Fire Department Connections are designed and manufactured in accordance with UL 405 - Standard for Fire Department Connections. We have two models, one is a straight type model LF-FDCG and a 90° type model LF-FDCI which casted from solid brass alloy to extend its service life.

Installation

The Fire Department Connection is provided with standard taper pipe threads which conforms to ANSI B2.1 and pin lug hose thread swivels for coupling hoses. Prior to installation, Apply pipe joint compound or PTFE tape on male threads, then, tighten it one full turn after tightening with hand, and make sure Connections are aligned accordance to the requirement.



Caps

The breakaway caps are supplied in brass alloy for the protection of 2½ inlets.



LF-FDCI

Technical Specification

Model	Size	Type	Work Pressure	Test Pressure	Installation	Swivel Thread
LF-FDCG	4x2.5x2.5	Straight	300 psi	600 psi	4" F.NPT	2-F.NH (NST)
LF-FDCI	4x2.5x2.5	90°	300 psi	600 psi	4" F.NPT	2-F.NH (NST)