

# VTET.EX28100 - Hose Cabinets, Racks and Reels

## Hose Cabinets, Racks and Reels

See General Information for Hose Cabinets, Racks and Reels

### LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

EX28100

UNIT 8, CALIBRE INDUSTRIAL PARK

LACHES CLOSE FOUR ASHES

WOLVERHAMPTON, WV10 7DZ UNITED KINGDOM

Semiautomatic Hose Rack Cabinet, Model LFD-HRC-150, for use with Models LFD-HRA-1515L, LFD-HRA-2515L, LFD-HRA-1515H or LFD-HRA-2515H hose rack assemblies and Models LFD-HR-1515L, LFD-HR-1515H, LFD-HR-2515L and LFD-HR-2515H hose racks.

Semiautomatic hose rack assembly, Model LFD-HRA-1515L, consisting of a separately Certified hose valve or pressure reducing valve (VTSR, VUTX), Model LFD-HR-1515L hose racks for use with interior standpipes systems of 1-1/2 in. size, respectively, for a maximum rated service pressure of 150 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes, rack nipple adapter and a portable spray hose nozzle (VUFZ).

Semiautomatic hose rack assembly, Model LFD-HRA-2515L, consisting of a separately Certified hose valve or pressure reducing valve (VTSR, VUTX), Model LFD-HR-2515L hose racks for use with interior standpipes systems of 2-1/2 in. size, respectively, for a maximum rated service pressure of 150 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes, rack nipple adapter and a portable spray hose nozzle (VUFZ).

Semiautomatic hose rack, Model LFD-HR-1515L, for use with interior standpipes systems of 1-1/2 in. size, for a maximum rated service pressure of 150 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes.

Semiautomatic hose rack, Model LFD-HR-2515L, for use with interior standpipes systems of 2-1/2 in. size, for a maximum rated service pressure of 150 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes.

Semiautomatic hose rack assembly, Model LFD-HRA-1515H, consisting of a separately Certified hose valve or pressure reducing valve (VTSR, VUTX), Model LFD-HR-1515H hose racks for use with interior standpipes systems of 1-1/2 in. size, respectively, for a maximum rated service pressure of 175 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes, rack nipple adapter and a portable spray hose nozzle (VUFZ).

Semiautomatic hose rack assembly, Model LFD-HRA-2515H, consisting of a separately Certified hose valve or pressure reducing valve (VTSR, VUTX), Model LFD-HR-2515H hose racks for use with interior standpipes systems of 2-1/2 in. size, respectively, for a maximum rated service pressure of 175 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes, rack nipple adapter and a portable spray hose nozzle (VUFZ).

Semiautomatic hose rack, Model LFD-HR-1515H, for use with interior standpipes systems of 1-1/2 in. size, for a maximum rated service pressure of 175 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes.

Semiautomatic hose rack, Model LFD-HR-2515H, for use with interior standpipes systems of 2-1/2 in. size, for a maximum rated service pressure of 175 psig, with a maximum of 100 ft of 1-1/2 in. lined (Mercedes MTL503, Fire Protection Products, Model 076 or Saudi Factory For Fire Equipment FZCO, Model SFD-FH-SJ40HR) fire hose for standpipes.

Last Updated on 2019-06-05

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"