

Fire Service Connections

A fire service pumper connection, located outside buildings, permits the fire service to pump water into a sprinkler system from a nearby public hydrant or reservoir. Water supplied at high pressure will aid automatic sprinklers to control a fire. The connection may also be used to supply building standpipes.

FM Approved connections are made of bronze and consist of two inlet couplings threaded for standard fire hose and siamesed into an outlet pipe connection. A check valve is provided in each inlet so that either connection may be used separately. The connections are available in straight, 45° or 90° patterns. Unless otherwise noted in the listing, these connections have 175 psi (1205 kPa) rated working pressure.

LF-FDCI, LF-FDCG

Model	Component Description	Nominal Size, Inlets x Outlet, in.	Rated Working Pressure psi, (kPa)
LF-FDCI	Single Check, 90° Siamese	2 1/2 x 2 1/2 x 4	300 (2070)
LF-FDCG	Single Check, Straightway Siamese	2 1/2 x 2 1/2 x 4	300 (2070)

Company Name:	Lichfield Fire & Safety Equipment Co Ltd
Company Address:	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
Company Website:	http://www.lifeco-uk.com
New/Updated Product Listing:	Yes
Listing Country:	United Kingdom
Certification Type:	FM Approved