

Valves, Alarm

COMPANY

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

UNIT 8, CALIBRE INDUSTRIAL PARK
 LACHES CLOSE FOUR ASHES
 WOLVERHAMPTON, WV10 7DZ United Kingdom

EX6005

Model A, 4 and 6 in. size alarm valves with flanged ends used with Model A retarding chamber and Model A water motor gong in vertical position.
 Models A, 3, 4, 6, 8 in. size for vertical installation only may be providing with constant pressure trim or variable pressure trim for use with Model RA rated chamber; Model GA water motor and gong.
 Model LF-WAV100BF, 4 in. size with flange-flange end configuration for rated pressures not exceeding 175 psig. For vertical installation.
 Model LF-WAV150BF, 6 in. size with flange-flange end configuration for rated pressures not exceeding 175 psig. For vertical installation.
 Model LF-WAV100PF, 4 in size with flange-flange end configuration for rated pressures not exceeding 200 psig. For vertical installation.
 Model LF-WAV150PF, 6 in. size with flange-flange end configuration for rated pressures not exceeding 200 psig. For vertical installation.
 Model LF-WAV100BG, 4 in size with groove-groove end configuration for rated pressures not exceeding 200 psig. For vertical installation.
 Model LF-WAV150BG, 6 in. size with groove-groove end configuration for rated pressures not exceeding 200 psig. For vertical installation.
 Model LF-WAV200A, 8 in. size with flange-flange and groove-groove end configurations for rated pressures not exceeding 250 psig. For vertical installation.

Alarm valves, Models BSAV, BSWM, BSRC.

Alarm valve, variable and constant pressure type							
LF-ACV-GG	Globe	2,2-1/2,2-1/2(76.1mm), 3,4,5(139.7mm),5,6(165.1mm),6,8(219.1mm),8,10,12	G by G	300		Water Motor Gong	V
						Electric pressure switch	
LF-ACV-FF	Globe	2,2-1/2,3,4,5,6,8,10,12	F by F (Class 125, Class 150, PN16)	300		Water Motor Gong	V
						Electric pressure switch	
LF-ACV-GF	Globe	2,2-1/2,2-1/2(76.1mm), 3,4,5(139.7mm),5,6(165.1mm),6,8(219.1mm),8,10,12	F by G (Class 125, Class 150, PN16)	300		Water Motor Gong	V
						Electric pressure switch	
LF-ACV-FG	Globe	2,2-1/2,2-1/2(76.1mm), 3,4,5(139.7mm),5,6(165.1mm),6,8(219.1mm),8,10,12	G by F (Class 125, Class 150, PN16)	300		Water Motor Gong	V
						Electric pressure switch	

- F - Flanged
- G - Grooved
- V - Vertical orientation

* End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

Last Updated on 2023-10-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."