




Classes of Fire



Description

Suitable to use on Class B and Electrical fires. The CO2 extinguisher is especially effective on electrical fires.

Technical & Specification

| Model | TC10 | TC25 | TC30 | TC60 | TC100 |
|-----------------------------|--------------------------------|-------|--------|---------|----------|
| Capacity | 10 Kg | 25 Kg | 30 Kg | 60 Kg | 100 Kg |
| Weight | 38 Kg | 96 Kg | 102 Kg | 195 Kg | 124.6 Kg |
| Height (mm) | 1025 | 1420 | 1420 | 1300 | 1650 |
| Width (mm) | 440 | 590 | 590 | 800 | 260 |
| Depth (mm) | 940 | 1310 | 1310 | 1600 | 1500 |
| Hose Length (mm) | 3500 | 3500 | 3500 | 5500 | 6000 |
| Maximum Effective Range (m) | 4 | 6 | 6 | 6 | 6 |
| Duration of Discharge (Sec) | 40-50 | 75-80 | 90-94 | 100-110 | 110-120 |
| Extinguishing Agent | CO2 | | | | |
| Testing Pressure (Bar) | 250 | | | | |
| Coating | Electrostatic Polyester Powder | | | | |
| Storage Temperature | -20°C to +60°C | | | | |