


**Classes of Fire**

**Description**

Suitable to use on Class B and Electrical fires. The CO<sub>2</sub> extinguisher is especially effective on electrical fires.

**Technical & Specification**

Extinguisher Type	Stored Pressure					Cartridge Operated		
	TF25	TF10G	TF50	TF100	TF35G	TFC50	TFC100	TFC35G
Model	TF25	TF10G	TF50	TF100	TF35G	TFC50	TFC100	TFC35G
Capacity	25 Ltr	37.8 Ltr	50 Ltr	100 Ltr	132 Ltr	50 Ltr	100 Ltr	132 Ltr
Weight	51.5 Kg	63 Kg	82 Kg	151 Kg	202 Kg	93 Kg	175 Kg	219 Kg
Height (mm)	990	1120	1010	1100	1341	1010	1100	1341
Width (mm)	455	450	555	700	555	555	700	700
Depth (mm)	665	400	695	900	1078	695	900	1078
Hose Length (mm)	3000	3000	5000	5000	5000	5000	6500	6500
Maximum Effective Range (m)	8	8	8	8	8	8	8	8
Duration of Discharge (Sec)	19-23	29-33	38-42	77-82	100-105	42-45	82-85	110-120
Extinguishing Agent	AFFF							
Propelling Agent	N <sub>2</sub>					CO <sub>2</sub>		
Working Pressure	12-15 Bar							
Testing Pressure	30 Bar							
Coating	Electrostatic Polyester Powder							
Storage Temperature	5°C to 60°C							