

Valves | Single Check Valves | **Check Valves, Single**

Models **LF-CVFF** **LF-CVGG** **LF-CVGGD**

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
LF-CVFF	Swing Check Valve, Flanged	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	365	(2515)	a, c
LF-CVGG	Swing Check Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	365	(2515)	a, c
LF-CVGGD	Swing Check Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	365	(2515)	a, b, c

Remarks:

- a. Resilient Seat
- b. Threaded drain connection located on the bottom of the valve body.
- c. For use in horizontal and vertical installations

Details

Category	Check Valves, Single
Class of Work	1210 - Single Check Valves
Approval Standard	FM 1210 - Swing Check Valves
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Lichfield Fire & Safety
Equipment Co Ltd
Edmund House, 12~22 Newhall
Street, Birmingham, B3 3AS,
United Kingdom