



Detection, Fire Alarm and Signaling Equipment | Sprinkler Valve Position Devices | **Sprinkler System Supervision, Standard Security**

# LF-SIP-1, LF-SIP-2, LF-SIP-3

## Product Description

Physical/Operating Specifications	LF-SIP-1	LF-SIP-2	LF-SIP-3
Differential	Single switch	Double switch	Double switch with Cover Tamper Switch
Switch Contact Ratings	10A@125/250VAC 2.5A@30VDC	10A@125/250VAC 2.5A@30VDC	10A@125/250VAC 2.5A@30VDC
Connection	1/2" NPT Male	1/2" NPT Male	1/2" NPT Male
Dimensions	L*W*H (11.6cm*6.0cm*15.0cm)	L*W*H (11.6cm*6.0cm*15.0cm)	L*W*H (11.6cm*6.0cm*15.0cm)
Operating Temperature Range	-40° to 60°	-40° to 60°	-40° to 60°
Cover Tamper Switch	No	No	Yes
Protection	IP67	IP67	IP67

## Details

<b>Category</b>	Sprinkler System Supervision, Standard Security
<b>Class of Work</b>	3132 - Water Pressure Sw
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United Kingdom

## Company

**Lichfield Fire & Safety Equipment Co Ltd**  
 Unit 8 Calibre Industrial Park,  
 Laches Close, Four Ashes,  
 Wolverhampton, Staffordshire  
 WV10 7DZ  
<http://lifeco-uk.com>