



Detection, Fire Alarm and Signaling Equipment | Sprinkler Valve Position Devices | **Sprinkler System Supervision, Standard Security**

LF-SSOSY-1, LF-SSOSY-2, LF-SSOSY-3

Product Description

<i>Physical/Operating Specifications</i>	LF-SSOSY-1	LF-SSOSY-2	LF-SSOSY-3
Differential	Single switch	Double switch	Double switch with Cover Tamper Switch
Switch Contact Ratings	10A@125/250VAC 2.5A@30VDC	10A@125/250VAC 2.5A@30VDC	10A@125/250VAC 2.5A@30VDC
Connection	Bolt	Bolt	Bolt
Dimensions	L*W*H (16.0cm*6.0cm*15.0cm)	L*W*H (16.0cm*6.0cm*15.0cm)	L*W*H (16.0cm*6.0cm*15.0cm)
Operating Temperature Range	-40° to 60°	-40° to 60°	-40° to 60°
Cover Tamper Switch	No	No	Yes
Protection	IP67	IP67	IP67

Details

Category	Sprinkler System Supervision, Standard Security
Class of Work	3132 - Water Pressure Sw
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Lichfield Fire & Safety Equipment Co Ltd
 Unit 8 Calibre Industrial Park,
 Laches Close, Four Ashes,
 Wolverhampton, Staffordshire
 WV10 7DZ
<http://lifeco-uk.com>