

## Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models 2905-300-LF, 2305-300-LF

<b>Model Number</b>	<b>Product Type</b>	<b>Nominal Pipe Size, inch (mm)</b>	<b>Rated Working Pressure, psi (kPa)</b>	<b>Remarks</b>
2905-300-LF	Butterfly Valve, Grooved Ends	2, 2-1/2, 3, 4, 5, 6 (50, 65, 80, 100, 125, 150)	300 (2070)	a, b, c
2305-300-LF	Butterfly Valve, Wafer Style	2, 2-1/2, 3, 4, 5, 6 (50, 65, 80, 100, 125, 150)	300 (2070)	a, b, c

**Remarks:**

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor service.
- c. FM Approved for aboveground installations only.

<b>Company Name:</b>	Lichfield Fire & Safety Equipment Co Ltd
<b>Company Address:</b>	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
<b>Company Website:</b>	<a href="http://www.lifeco-uk.com">http://www.lifeco-uk.com</a>
<b>New/Updated Product Listing:</b>	Yes
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved