



Classes of Fire



Technical Specification

Agent	Water + Additive
Capacity	9 Ltr
Propellant	Nitrogen
Operation Temperature	-15°C ~ +60°C
Working Pressure	12 Bar
Test Pressure	27 Bar
Discharge Time	36.0 Sec
Range of Throw	>5 mtr
Hose Type	PVC13
Length	520 mm
Height	534 mm
Diameter	163 mm
Filled Weight	13.78 kg
Material	Low-Carbon Steel

Fire Rating

A	B	C	D	E	F
55	183	X	X	✓	75

Description

Water + additive extinguishes by cooling the fire and is the simple, conventional and ever-faithful extinguishing agent.

Features

- EN3 Kitemark approval by BSI in the UK
- Above average fire ratings offering maximum fire fighting ability with minimum size and weight
- Specially designed nozzle for best discharge application, accuracy and time
- Easy to use for untrained operator
- Easy to refill onsite
- Available in 2, 6 & 9 Ltrs

Precaution

- It is not SAFE to use on electrical fires
- Not suitable for C, D and E or any other risk fires

Industries of Use

- Offices
- Storage & Archive facilities
- Timber Industry
- Paper industry
- Retail
- Restaurants
- All canteens (schools, universities, military, factories)
- Hotel kitchens
- Food factory and processing plants