



Classes of Fire



Description

Automatic Foam Extinguishers (AFFF – Aqueous Film Forming Foam) works by firstly applying a film forming foam (bubbles) to the fire which causes a blanket over the fire, suffocating the fire, while almost simultaneously cooling the fire.

Technical & Specification

Model	LFFX4.5 MATIC	LFFX6 MATIC	LFFX10 MATIC	LFFX12 MATIC	LFFX15 MATIC	LF FX20 MATIC	LF FX25 MATIC	LF FX30 MATIC
Capacity	2.5 Ltr	6 Ltr	10 Ltr	12 Ltr	15 Ltr	20 Ltr	25 Ltr	30 Ltr
Weight	10.56 Kg	12.06 Kg	19 Kg	22.92 Kg	26 Kg	34 Kg	41 Kg	47 Kg
Height (mm)	400	400	460	485	555	525	470	575
Width (mm)	162	162	280	305	370	340	320	390
Depth (mm)	280	280	280	280	280	360	360	360
Hose Length (mm)	20-28	25-30	50-60	60-90	90-120	120-150	150-180	180-210
Maximum Effective Range (m)	AFFF							
Duration of Discharge (Sec)	N2							
Extinguishing Agent	12-15							
Testing Pressure (Bar)	30							
Coating	Electrostatic Polyester Powder							
Storage Temperature	5°C to 60°C							