

## Flexible Sprinkler Hose with Fittings

### COMPANY

#### LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

UNIT 8, CALIBRE INDUSTRIAL PARK

LACHES CLOSE FOUR ASHES

WOLVERHAMPTON, WV10 7DZ United Kingdom

EX26691

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
LPB-B700-12	200	225	1x1/2	2.3 (700)	2	4	26	Limited
LPB-B1000-12	200	225	1x1/2	3.3 (1000)	3	4	45	Limited
LPB-B1200-12	200	225	1x1/2	3.9 (1200)	3	4	51	Limited
LPB-B1500-12	200	225	1x1/2	4.9 (1500)	3	4	66	Limited
LPB-B1800-12	200	225	1x1/2	5.9 (1800)	3	4	69	Limited
LPB-B700-19	200	225	1x3/4	2.3 (700)	2	4	31	Limited
LPB-B1000-19	200	225	1x3/4	3.3 (1000)	3	4	50	Limited
LPB-B1200-19	200	225	1x3/4	3.9 (1200)	3	4	55	Limited
LPB-B1500-19	200	225	1x3/4	4.9 (1500)	3	4	70	Limited
LPB-B1800-19	200	225	1x3/4	5.9 (1800)	3	4	74	Limited
LPN-A700-12	200	225	1x1/2	2.3 (700)	2	4	26	Limited
LPN-A1000-12	200	225	1x1/2	3.3 (1000)	3	4	45	Limited
LPN-A1200-12	200	225	1x1/2	3.9 (1200)	3	4	51	Limited
LPN-A1500-12	200	225	1x1/2	4.9 (1500)	3	4	66	Limited
LPN-A1800-12	200	225	1x1/2	5.9 (1800)	3	4	69	Limited
LPN-A700-19	200	225	1x3/4	2.3 (700)	2	4	31	Limited
LPN-A1000-19	200	225	1x3/4	3.3 (1000)	3	4	50	Limited

LPN-A1200-19	200	225	1x3/4	3.9 (1200)	3	4	55	Limited
LPN-A1500-19	200	225	1x3/4	4.9 (1500)	3	4	70	Limited
LPN-A1800-19	200	225	1x3/4	5.9 (1800)	3	4	74	Limited
LPB-D700-12	200	225	1x1/2	2.3 (700)	2	4	33	Limited
LPB-D1000-12	200	225	1x1/2	3.3 (1000)	3	4	57	Limited
LPB-D1200-12	200	225	1x1/2	3.9 (1200)	3	4	68	Limited
LPB-D1500-12	200	225	1x1/2	4.9 (1500)	3	4	82	Limited
LPB-D1800-12	200	225	1x1/2	5.9 (1800)	3	4	98	Limited
LPB-D700-19	200	225	1x3/4	2.3 (700)	2	4	38	Limited
LPB-D1000-19	200	225	1x3/4	3.3 (1000)	3	4	62	Limited
LPB-D1200-19	200	225	1x3/4	3.9 (1200)	3	4	73	Limited
LPB-D1500-19	200	225	1x3/4	4.9 (1500)	3	4	89	Limited
LPB-D1800-19	200	225	1x3/4	5.9 (1800)	3	4	104	Limited
LPN-C700-12	200	225	1x1/2	2.3 (700)	2	4	33	Limited
LPN-C1000-12	200	225	1x1/2	3.3 (1000)	3	4	57	Limited
LPN-C1200-12	200	225	1x1/2	3.9 (1200)	3	4	68	Limited
LPN-C1500-12	200	225	1x1/2	4.9 (1500)	3	4	82	Limited
LPN-C1800-12	200	225	1x1/2	5.9 (1800)	3	4	98	Limited
LPN-C700-19	200	225	1x3/4	2.3 (700)	2	4	38	Limited
LPN-C1000-19	200	225	1x3/4	3.3 (1000)	3	4	62	Limited
LPN-C1200-19	200	225	1x3/4	3.9 (1200)	3	4	73	Limited
LPN-C1500-19	200	225	1x3/4	4.9 (1500)	3	4	89	Limited
LPN-C1800-19	200	225	1x3/4	5.9 (1800)	3	4	104	Limited

Braided flexible sprinkler hose with fittings, LPB-B series are intended to be installed with the S1 and L2 bracket combination in accordance with the manufacturer's installation instructions revised 2019-05-28.

Braided flexible sprinkler hose with fittings, LPB-D series are intended to be installed with the S2-1 and L2 bracket combination in accordance with the manufacturer's installation instructions revised 2019-05-28.

Unbraided flexible sprinkler hose with fittings, LPN-A series are intended to be installed with the S1 and L2 or S2 and L2-2 bracket combination in accordance with the manufacturer's installation instructions revised 2021-07-12.

Unbraided flexible sprinkler hose with fittings, LPN-C series are intended to be installed with the S2-1 and L2 bracket combination in accordance with the manufacturer's installation instructions revised 2019-05-28.

Trademark and/or Tradename:  , "LIFECO"

Last Updated on 2021-07-19

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."