

## Sprinkler System Alarm Testers

Each separate sprinkler system must be equipped with a separate waterflow alarm. In a high rise building, the system for each floor must be separately alarmed. Where pressure reducing valves are used, a dual alarm and drain piping arrangement is required. The alarm testers listed below combine test and drain valves, a waterflow sight glass, and a calibrated flow orifice in a single assembly to simplify the piping required for such arrangements.

### LIFECO Model LF-TD/25-UL/FM and LF-TD/32-UL/FM

<b>Model Designation</b>	<b>Size, inch NPS</b>	<b>Nominal K-factor(s)</b>	<b>Rated working pressure, psi (kPa)</b>	<b>Remarks</b>
LIFECO LF-TD/25-UL/FM	1	5.6	175 (1205)	a
LIFECO LF-TD/32-UL/FM	1 1/4	5.6	175 (1205)	a

**Remarks:**

a. Devices supplied with female threaded inlet and a male threaded outlet end connection.

<b>Company Name:</b>	Lichfield Fire & Safety Equipment Co Ltd
<b>Company Address:</b>	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
<b>Company Website:</b>	<a href="http://www.lifeco-uk.com">http://www.lifeco-uk.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved