

Hose Valves

COMPANY

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

UNIT 8, CALIBRE INDUSTRIAL PARK
LACHES CLOSE FOUR ASHES
WOLVERHAMPTON, WV10 7DZ United Kingdom

EX6012

Angle types, 1 1/2 in. with female/female ends, for working pressures not to exceed 300 psi, Model(s) AH-15

Angle types, 1 1/2 in. with female/male ends, for working pressures not to exceed 300 psi, Model(s) AH-20

Angle types, 2 1/2 in. with female/female ends, for working pressures not to exceed 300 psi, Model(s) AH-25

Angle types, 2 1/2 in. with female/male ends, for working pressures not to exceed 300 psi, Model(s) AH-30

Angle types, 1-1/2, with female/female (NPT/NPS) and female/male (NPS) ends. for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) LF-AH-20

Angle types, 2-1/2 in., with female/female (NPT/NPS), female/male (NPS), Female NPT/Male NYC, GRV by Male NH, GRV by Male NYC and Male NH by Male NYC for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) LF-AH-30

Angle types, 1-1/2, with female/female (NPT/NPS) and female/male (NPS) ends. for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) LF-AH-15

Angle types, 2-1/2 in., with female/female (NPT/NPS), female/male (NPS), Female NPT/Male NYC, GRV by Male NH, GRV by Male NYC and Male NH by Male NYC for a maximum working pressure of 300 psi, for use on a fire hose rack assembly, or as a fire department outlet connection, Model(s) LF-AH-25

Trademark and/or tradename:



Last Updated on 2022-09-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Feedback