

Pressure-reducing and -Restricting Devices

COMPANY

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD

UNIT 8, CALIBRE INDUSTRIAL PARK
LACHES CLOSE FOUR ASHES
WOLVERHAMPTON, WV10 7DZ United Kingdom

EX28846


Model	Valve Type	Body Type	NPS	Bonnet Type*	End Configuration Inlet by Outlet	Max Rated Inlet Pressure, psig	Supervisory Switch+
LF-RV-AH20	Restricting - Adjustable	Angle	1.5	—	Female X Male	175	—
LF-RV-AH15	Restricting - Adjustable	Angle	1.5		Female X Female	175	
LF-RV-AH30	Restricting - Adjustable	Angle	2.5	—	Female X Male	175	—
LF-RV-AH25	Restricting - Adjustable	Angle	2.5		Female X Female	175	

* Different bonnet configurations are selected based upon inlet pressure conditions and desired outlet pressure.

+ I = Indoor installation; O = Outdoor installation

NPT - National Pipe Thread

Trademark and/or tradename:



Last Updated on 2022-09-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."