



SIDE VIEW

FRONT VIEW

Nominal Capacity (Gallons)	Length (mm) (A)	Dia (mm) (B)	C	D	E	F	G	H	I	J	(Radius) K
25	600	500	100	400	290	100	180	335	-	-	-
50	700	600	125	450	290	100	180	410	-	-	-
60	850	600	125	725	290	100	180	410	-	-	-
75	1050	600	125	800	290	100	180	410	-	-	-
90	1220	600	125	970	290	100	180	410	-	-	-
100	1220	650	150	920	290	100	180	430	-	-	-
125	1220	700	150	920	290	100	180	460	-	-	-
150	1220	777	150	920	290	100	180	460	-	-	-
200	2000	700	300	1400	290	100	180	460	-	-	-
210	2000	720	300	1400	290	100	180	460	-	-	-
250	2000	780	300	1400	290	100	180	530	-	-	-
300	2000	860	300	1400	290	100	180	565	-	-	-
350	2000	920	300	1400	-	-	-	-	871	530	468
400	2000	990	300	1400	-	-	-	-	924	542	503
450	2000	1050	300	1400	-	-	-	-	978	558	533
500	2000	1100	300	1400	-	-	-	-	1019	577	558
550	2000	1170	300	1400	-	-	-	-	1080	586	593
600	2000	1220	300	1400	-	-	-	-	1123	600	618
610	2000	1220	300	1400	-	-	-	-	1123	600	618
650	2150	1220	300	1550	-	-	-	-	1123	600	618

General note:

Tolerance ± 5mm.

All Dimensions are in Millimeters, unless specified.

Material :

- Shall be Carbon Steel, Stainless Steel, Mild Steel.

Nozzle details

1. Air vent Nozzle - 1 Inch
2. Level Indicator - 2 Inch
3. Filling Nozzle - 2 Inch
4. Spare Nozzle - 2 Inch
5. Drain Nozzle - 1 Inch
6. Outlet Nozzle - 1 Inch
7. Lift Lug



LICHFIELD
FIRE & SAFETY
EQUIPMENT
CO. LTD.
UNITED KINGDOM

TITLE:

**HORIZONTAL CYLINDRICAL
Non-UL DIESEL TANK**

Drawn by:	Checked By	Approved By	Date	Scale	Sheet No.	Rev.
ALPESH	ABDALLA	MOHAMMAD	22-02-2021	NTS	1	R0