



Coming October 20th, discover our sleek new design and powerful features.
[Learn More](#)

UL Product iQ®



System Unit LIFECO-55, IG-55 engineered extinguishing system units, 200 and 300 bar
File Number: EX15998

COMPANY

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD
Edmund House
12-22 Newhall Street
Birmingham, B3 3AS United Kingdom

SYSTEM UNIT INFO

LIFECO-55, IG-55 engineered extinguishing system units, 200 and 300 bar
Engineered, Inert Gas

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	IG-55

MANUALS AND BULLETINS		
Part No.	Description	Date/Rev
LFIGMAL-0055	Design, Installation, Operation and Maintenance Manual	May 2024 / 04

SYSTEM UNIT INFORMATION		
Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
200 bar @ 21°C	-20 C (-4 F)	55 C (131 F)
300 bar @ 21°C	-20 C (-4 F)	55 C (131 F)

THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:**Software Name/Version**

LIFECO Flow Calculation Software v4.10

Report Date: 2025-10-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."