

1. PRODUCT OVERVIEW

The LF-ELDR3 is a high-performance, addressable monitoring type emergency down light (Round) designed for discreet and effective safety lighting. Featuring high-output SMD LEDs and a reliable Lithium battery system, it provides high-intensity illumination during power outages.



2. TECHNICAL SPECIFICATIONS

Feature	Specification
Product Model	LF-ELDR3
Battery	Li 3.7V / 2200mAH
Emergency Duration	3 Hours
Charge Time	24 Hours
Input Voltage	DC 36V
Input Power	3.5W
Input Current	95mA
Operation Mode	Maintained / Non-Maintained
Emergency Power	2.1W

3. OPTICAL CHARACTERISTICS

Feature	Specification
LED Package Type	SMD 3535
LED Quantity	2 pcs
Color Temperature (CCT)	5700K - 7200K
Luminous Flux (DC 36V)	>= 300 lm
Emergency Luminous Flux	>= 300 lm
Color Rendering Index (CRI)	>= 70

4. STRUCTURAL & INSTALLATION

Construction

- **Housing Material:** PBT 5VA + AL6063 (Aluminium)
- **Cover Material:** PBT 5VA
- **Case Color:** White
- **Dimensions:** 142.5 mm Diameter x 48 mm
- **PCB Type:** FR4 / 1.2mm & 2.0mm

Protection & Classification

- **Degree of Protection:** Dry Location
- **Classification:** Class II
- **Operation Temperature:** 0 to 40 Degrees Celsius

Mounting Options

- Surface Mount
- Recessed Mount

5. CERTIFICATION & COMPLIANCE

- **Standard:** UL 924 Listed
- **ML File No:** E474559

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD (LIFECO)

LIFECO Emergency Systems - Product Code: LF-ELDR3 | Revision: 2026.01