

1. PRODUCT OVERVIEW

The **LF-ELB3** is a high-performance, addressable monitoring type emergency light designed for demanding safety applications. Featuring a robust IP65-rated housing for dust and water resistance, energy-efficient SMD LED technology, and a Reliable Lithium battery system, it provides high-intensity safety illumination for both indoor and outdoor environments.



2. TECHNICAL SPECIFICATIONS

| Feature | Specification |
|--------------------|-----------------------------|
| Product Model | LF-ELB3 |
| Battery | Li 3.7V / 1500mAH |
| Emergency Duration | 3 Hours |
| Charge Time | 24 Hours |
| Input Voltage | DC 36V |
| Input Power | 3.5W |
| Input Current | 95mA |
| Operation Mode | Maintained / Non-Maintained |
| Emergency Power | 1.7W |

3. OPTICAL CHARACTERISTICS

| Feature | Specification |
|-----------------------------|---------------|
| LED Package Type | SMD 2835 |
| LED Quantity | 22 pcs |
| Color Temperature (CCT) | 5700K - 7200K |
| Luminous Flux (Main Power) | >= 225 LM |
| Emergency Luminous Flux | >= 225 LM |
| Color Rendering Index (CRI) | >= 70 |

4. STRUCTURAL & INSTALLATION

Construction

- Housing Material:** Polycarbonate (PC)
- Cover Material:** Polycarbonate (PC)
- Case Color:** White
- Dimensions:** 352 mm x 110 mm x 68 mm
- PCB Type:** FR-4 / 1.6mm

Protection & Classification

- Degree of Protection:** IP65 (Weatherproof)
- Classification:** Class 2



- **Operation Temperature:** 0 to 40 Degrees Celsius

Mounting Options

- Surface Mount

5. CERTIFICATION & COMPLIANCE

- **Standard:** UL 924 Listed
- **ML File No:** E474559

LICHFIELD FIRE & SAFETY EQUIPMENT CO LTD (LIFECO)

LIFECO Emergency Systems - Product Code: LF-ELB3 | Revision: 2026.01

