

Valves | Angle Hose Valves | [Hose Valves, Angle](#)

LF-AVPR15, LF-AVPR20, LF-AVPR25, LF-AVPR30

Product Description

Product Specification

Model No	Description	Valve Size		Rated Working Pressure	
		in	(mm)	psi	(kPa)
LF-AVPR15	Pressure Restricting Hose Valve Female NPT x Female NPT	1 1/2	(38)	300	(2065)
LF-AVPR20	Pressure Restricting Hose Valve Female NPT x Male NH	1 1/2	(38)	300	(2065)
LF-AVPR25	Pressure Restricting Hose Valve Female NPT x Female NPT	2 1/2	(64)	300	(2065)
LF-AVPR30	Pressure Restricting Hose Valve Female NPT x Male NH	2 1/2	(64)	300	(2065)

Details

Category	Hose Valves, Angle
Class of Work	1521 - Angle Hose Valves
Approval Standard	FM 1521, 1522 - Angle and Straightaway Hose Valves
Certification Type	FM Approved
Listing Country	United Kingdom

Company

**Lichfield Fire & Safety
Equipment Co Ltd**
Edmund House, 12~22 Newhall
Street, Birmingham, B3 3AS,
United Kingdom

FM Approvals

Additional Info

Hydrants & Hoses

Hose Valves

Hose valves of 1 ½ in. (38 mm) may be used on connections from sprinkler systems; 2 ½ in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle
